

PROFESSIONAALSED PUHASTUSAINED

Drive PTL

Pre-soak

RANGE OF USAGE: Pre-soak for removing all types of dirt, including grease and oil

and tar from vehicles, cars, terpaulins and also from repair shops floors. Suitable for pre-wash at winter time. Suitable for wahing motors, ship's stovepipe and other where is hard-to-remove dirt

problem.

PROPERTIES: With big foam pre-soak contains effective surfactants and rust

inhibitors. Drive PTL keeps clean the brushes in tunnel car washing machines. Thoroughly and gently eradicates tar and oil stains, as well as other stubborn dirt. Do not contain petrooleum

based solvents and phosphates.

PACKAGE: 25 I plastic canister, 200 I barrel

DOSAGE: 1:3 – 1:50

INSTUCTIONS FOR USAGE: Spray PTL solution onto surface to be treated. Start from the

bottom of car and go upwards. Let the solution to work 2 to 10 minutes before treating surface with a sponge, brush or pressure washer. Rinse with water. NB! Do not allow the surface to dry.

COMPOSITION: Anionic surfactants 5-15%, nonionic surfactants >5%.

pH: Usage solution pH 12

PRECAUTIONARY MEASURES: Harmful to aquatic life with long lasting effects. Causes serious

eye damage. Causes skin irritation. Avoid release to the

environment. Wear protective gloves/eye protection. Wash with plenty of water. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediately call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. Dispose of contents and / or containers in accordance with regulations on hazardous waste or

packaging and packaging waste respectively.

ENVIRONMENT: Avoid release to the environment. The package is from PE; clean

package can be recycled. A clean, empty canister can may be

disposed of by burning.

11/2017



